

Product News Backup Wrench

Applications

- **alkitronic® backup wrench** prevents self-holding the nuts from spinning during the tightening and loosening of a bolt. To release the tension over the adjusting screw, easily and quickly remove the backup wrench, which is clamped firmly against the support after mounting.
- The support on the backup wrench is fixed with a bolt. After tightening the fixation bolt must be loosened and the backup wrench released. This method is the most flexible and secure one.
- The **alkitronic® backup wrench** consists of a handle and a cartridge with different AF sizes.

Advantages

- The **alkitronic® backup wrench** with the cartridges has less total weight than a one-piece construction.
- Strong and sturdy version for robust working
- Ergonomic and safe handling
- Compact design
- Mechanical function – no hydraulic
- After the application easy and simple detachment
- For use with or without handle
- Waiving inadequate tightening/loosening using screwdrivers, clamping tongs, socket spanners, etc.



Technical Data / Standard Products

Cartridges AF (mm)

46	50	55	60	65	70
75	80	85	90	95	100

Other AF sizes on request



alkitronic® backup wrench in use on the bolt circle in a wind power plant.



alkitronic® backup wrench with handle.

alkitronic®

TORQUE POWER WORLDWIDE

alkitronic® products
Made in Germany by

alki TECHNIK GmbH
Development, Production and
Distribution of Bolting Systems

Unterlettenweg 4
85051 Ingolstadt/Germany

fon + 49 841 97499-0
fax + 49 841 97499-90
info@alkitronic.com
www.alkitronic.com